

## SHOP SUPPLIES

### FASTENERS

#### Square Drive Pan Head Kwik Drill Screws

- Self-drilling screws
- Zinc plated
- Fully threaded



| PART #     | LEGACY # | SIZE        | QTY. |
|------------|----------|-------------|------|
| 102738575* | 106877   | #6 x 1/2    | 100  |
| 102748260* | 106884   | #8 x 1/2    | 100  |
| 102738576* | 106887   | #8 x 1      | 100  |
| 102736165* | 106893   | #10 x 1/2   | 100  |
| 116681717* | 106896   | #10 x 1     | 100  |
| 102261676* | 106897   | #10 x 1-1/4 | 100  |

### BATTERY TERMINALS

#### Twist Tight Terminals

- These 4 ga. and 2/0 battery terminals can be installed on 2/0 battery cable without crimping tools or solder (cannot be used with welding cable).
- Terminals are cast with 131 contact copper (93-95% copper) to ensure malleability and high conductivity
- Exceeds SAE conductivity standard J163
- Electro-tin plating for complete coverage, better appearance, high conductivity and corrosion resistance
- Raised lettering for easy identification of polarity and wire size
- Extra deep chamfer helps wire installation
- The inside of the barrel is threaded with two distinct stages of threads. The thread grabs the bare wire, and when tightened it gives an incredible pullout strength.
- Installation is done using only a screw driver and vice
- Installation is completed quickly and easily



| PART #    | LEGACY # | DESCRIPTION                            | DIE CODE SETTING | QTY. |
|-----------|----------|--|------------------|------|
| 116682955 | 404440   | 4 Ga. Universal Post Type Straight     | Green            | 5    |
| 116682957 | 404441   | 4 Ga. Negative Post Type Straight      | Green            | 5    |
| 116682962 | 404442   | 4 Ga. Universal Side/Top Mount         | Green            | 5    |
| 116682964 | 404443   | 2/0 Neg. Post Type Straight            | Orange           | 5    |
| 116682967 | 404444   | 2/0 Pos. Post Type Straight            | Orange           | 5    |
| 116682969 | 404445   | 2/0 Univ. Stackable Single Barrel      | Orange           | 5    |
| 116682972 | 404446   | 2/0, 3/8 Heavy Duty Copper Starter Lug | Orange           | 5    |



\* While supplies last

### SAFETY

#### Showa<sup>®</sup> N-DEX 7005 Blue 4 Mil Lightly Powdered Nitrile Gloves

- Perfect for cleanup crews that make contact with mold, debris, and bugs
- Reduces hand fatigue through its second-skin feel
- Durable 4-Mil thickness
- Lightly powdered
- Length: 9.5 inches
- 100 gloves/box



| PART #     | LEGACY # | SIZE | QTY. |
|------------|----------|------|------|
| 102645853* | 124178   | L    | 1    |
| 102651896* | 124179   | XL   | 1    |

#### MCR Safety<sup>®</sup> Predator<sup>®</sup> Series Full Smooth Nitrile Coated Work Gloves

- Component materials comply with all relevant federal regulations for food contact
- Fully coated with premium nitrile
- Safety cuff for added protection
- Soft jersey and foam lining
- Treated with ActiFresh<sup>®</sup>



| PART #    | LEGACY # | SIZE | QTY. |
|-----------|----------|------|------|
| 116741197 | MCR9770  | L    | 1    |

### PAINT

#### Spray Sock

- Provides comfortable protection against over spray & other particulates
- Fits over head and can be worn with goggles, half mask or full mask respirators
- Made of stretch knit material that is breathable and cool to wear



| PART #    | LEGACY # | COLOR   | SIZE               | QTY. |
|-----------|----------|---------|--------------------|------|
| 110489173 | PA92416  | Natural | One Size Fits Most | 12   |



## FITTINGS

### Dixon Air King™ "Chicago" 2-Lug Couplings X Female Pipe

- Malleable iron
- Made in the USA
- Includes gasket, safety clip
- Pressure rating: 150 PSI
- Gasket temperature range: -20°F to +160°F
- Air & water service only – do not use with steam
- Use of safety clip is necessary to insure Chicago couplings will not become accidentally disconnected



| PART #    | LEGACY # | DESCRIPTION              | SIZE      | DIXON # | QTY. |
|-----------|----------|--------------------------|-----------|---------|------|
| 106257772 | PA87944  | Female NPT End x Chicago | 3/8" FNPT | AMC     | 5    |
| 106277993 | PA87945  | Female NPT End x Chicago | 1/2" FNPT | AM3     | 5    |
| 106297013 | PA87946  | Female NPT End x Chicago | 3/4" FNPT | AM8     | 5    |
| 116759235 | PA87947  | Female NPT End x Chicago | 1" FNPT   | AM13    | 5    |

### Dixon Air King 4-Lug Couplings X Female Pipe

- Air & water service only – do not use with steam
- Malleable iron
- Made in the USA
- Use of safety clip is necessary to insure 4-Lug couplings will not become accidentally disconnected



| PART #    | LEGACY # | DESCRIPTION            | SIZE        | DIXON # | QTY. |
|-----------|----------|------------------------|-------------|---------|------|
| 116771075 | DX-AM18  | Female NPT End x 4-Lug | 1-1/4" FNPT | AM18    | 1    |
| 116771093 | DX-AM23  | Female NPT End x 4-Lug | 1-1/2" FNPT | AM23    | 1    |
| 116771103 | DX-AM28  | Female NPT End x 4-Lug | 2" FNPT     | AM28    | 1    |

### Safety Clip

| PART #    | LEGACY # | DESCRIPTION | SIZE      | DIXON # | QTY. |
|-----------|----------|-------------|-----------|---------|------|
| 106292072 | PA88799  | Safety Clip | All Sizes | AC1     | 10   |



**⚠ WARNING:** Cancer and Reproductive Harm-[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



### DID YOU KNOW

The Romans used a form of coupling in their aqueducts and water

system. Though, these couplings were simpler than the 4-lug couplings we use on today.

The Romans crafted clamps from bronze or lead that would secure connections between pipes, ensuring a smooth flow of water and prevent leaks. Unlike the threaded and lugged designs we're familiar with, Roman clamps likely relied on a simpler approach, using friction or a wedging mechanism to hold the pipes together. These clamps represent one of the earliest steps in the evolution of coupling technology, paving the way for the more complex designs we use today.



Digital Catalog available at [Catalog.AppliedMSS.com](http://Catalog.AppliedMSS.com) and in the Google and Android App stores.



**Every Small Part Counts** We're here to manage them for you!®

**AppliedMSS.com | 800-458-4018**

