

## PTFE Tapes

### Poly-Temp® XHD PTFE Tape

Poly-Temp® Thread Seal Tapes are 100% PTFE from the highest quality resins available. This universal thread sealant can be used on all types of metal or plastic pipe connections and effectively seal a vast array of chemicals. Suitable for oxygen systems.



- Lubricates threads for easy assembly
- Chemically inert, non-toxic
- Made with resins compliant with FDA 21 CFR 177.1550
- Exceeds MIL-T-27730A, meets Spec C.I.D. A-A 58092
- UL Listed
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi

PART #	SIZE	DENSITY	QTY.
120582367	1-1/2" X 520'	1.2 - 1.5 g/cc	2
120582366	1" X 520'	1.2 - 1.5 g/cc	2
120582365	3/4" X 520'	1.2 - 1.5 g/cc	5
120582364	1/2" X 520'	1.2 - 1.5 g/cc	5

### Poly-Temp® SSG (XHD) Stainless Steel Grade PTFE Tape

Poly-Temp® Thread Seal Tapes are 100% PTFE from the highest quality resins available. This universal thread sealant can be used on all types of metal or plastic pipe connections and effectively seal a vast array of chemical.



- Lubricates threads for easy assembly
- Chemically inert, non-toxic
- Exceeds MIL-T-27730A, meets Spec C.I.D. A-A 58092
- UL Listed
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi

PART #	SIZE	DENSITY	QTY.
120582380	1/2" X 260'	1.2 - 1.5 g/cc	5

**⚠ WARNING:** This product can expose you to nickel, which is known to the State of California to cause cancer. For more information to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).

### Poly-Temp® Gas (XHD), Yellow Gas Line PTFE Tape

The same material as the Poly-Temp® XHD (our highest grade of PTFE tape) extra thick and extra density material, has approval from the CSA (Canadian Standards Association) for gas lines (CSA #4-90).



- Chemically inert, non-toxic
- UL listed
- Made with resins compliant with FDA 21 CFR 177.1550
- Exceeds MIL-T- 27730A, Meets C.I.D. A-A 58092
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi

PART #	SIZE	DENSITY	QTY.
120582383	3/4" X 520'	1.2 - 1.5 g/cc	5
120582382	1/2" X 520'	1.2 - 1.5 g/cc	5
120582381	1/2" X 260'	1.2 - 1.5 g/cc	5

### Poly-Temp® PNK (XHD), Pink Plumber's Tape

Pink Plumber's PTFE Tape is a full density PTFE thread seal tape especially designed for professional plumbers. The pink color distinguishes itself from low-grades of PTFE tapes. Suitable for demanding industrial and commercial plumbing applications. Strong and durable with positive sealing for tough applications. Recommended for galvanized pipe, copper, brass, chrome, or other plated pipe.



- Chemically inert, non-toxic
- Meets MIL 27730A C.I.D. A-A 58092
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi

PART #	SIZE	DENSITY	QTY.
120582384	1/2" X 260'	1.2 - 1.5 g/cc	5



## Poly-Temp® Ceramic Tape, Food Grade

Formulated specifically for anti-seize applications typical to the food industry. All materials are FDA approved.

- Discourages seizing, galling, and carbon fusing
- Compatible with a wide range of chemicals
- Non-flammable, non-staining
- Inhibits corrosion, rusting, and galvanic pitting
- Excellent pipe thread sealant up to 550°F (288°C)
- POLY-TEMP® Ceramic Tape is made from resins that meet the FDA requirement 21 CFR 177.1550
- Color: Off-white



PART #	SIZE	QTY.
120582363	3/4" X 600'	1
120582362	1/2" X 600'	1



## Poly-Temp® Heavy Duty PTFE Tape

- Chemically inert, non-toxic
- Made with resins compliant with FDA 21 CFR 177.1550
- Meets MIL-T-27730A
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi
- DEF (Diesel Exhaust Fuel) Compatible



PART #	SIZE	DENSITY	QTY.
120582370	3/4" X 520'	0.9 - 1.1 g/cc	5
120582369	1/2" X 520'	0.9 - 1.1 g/cc	5
120582368	1/2" X 260'	0.9 - 1.1 g/cc	5

POLY-TEMP® is a registered trademark of Anti-Seize Technology

## Poly-Temp® MD PTFE Tape

Its medium density allows it to be used as a general-purpose thread seal tape in most applications. May be used on all types of pipes and most services. More economical than most paste thread-sealing compounds, never dries out, no mess, no dripping, easy to apply.



- Chemically inert, non-toxic
- Made with resins compliant with FDA 21 CFR 177.1550
- Meets MIL-T-27730A
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi

PART #	SIZE	DENSITY	QTY.
120582375	1" X 520'	0.7 - 0.8 g/cc	5
120582374	3/4" X 520'	0.7 - 0.8 g/cc	5
120582372	1/2" X 520'	0.7 - 0.8 g/cc	5
120582373	1/2" X 520'	0.7 - 0.8 g/cc	10
120582371	1/2" X 260'	0.7 - 0.8 g/cc	5

## Low Density PTFE Thread Seal Tape

This tape remains flexible, is a thread sealant for all services and non-hardening. This universal thread sealant can be used on all types of metal or plastic pipe connections and effectively seal a vast array of chemicals.



- Chemically inert, non-toxic
- Made with resins compliant with FDA 21 CFR 177.1550
- Meets MIL-T-27730A
- Temperatures from -400° to 550°F (-240° to 287°C)
- Pressures up to 10,000 psi

PART #	SIZE	DENSITY	QTY.
120582379	1" X 520'	0.35 - 0.5 g/cc	5
120582378	3/4" X 520'	0.35 - 0.5 g/cc	5
120582377	1/2" X 520'	0.35 - 0.5 g/cc	5
120582376	1/2" X 260'	0.35 - 0.5 g/cc	5

