



MRO Solutions to Keep Your Marina Shipshape

Whether you're gearing up to winterize boats, taking extra precautions during hurricane season or managing a busy marina day-to-day, Applied MSSSM has you (and your boats) covered.



MARINA MAINTENANCE CHECK LIST:



Clean equipment

Inspect all areas for safety concerns, wear or damage

Identify inventory needs for all hardware

Inspect electrical system regularly

Install safety equipment



TOP PRODUCTS FOR MARINAS

AERO-CHEM® PTFE GEL PENETRATING LUBRICANT

- A clear penetrating lubricant that sprays out as a penetrating fluid and sets up to form a tough, heat resistant grease
- Contains PTFE for long lasting lubricity
- Resists water washout
- Temperature range: -30°F to 600°F (-34°C to 316°C)
- Recommended for open gears, wire ropes, conveyors, chains, etc.

PART #	LEGACY #	DESCRIPTION	QTY.
106273082	PA86208	20oz. Can/14 oz. net wt. (397g)	1
116758342	PA86208-12	20oz. Can/14 oz. net wt. (397g)	12
116758346	PA86208-24	20oz. Can/14 oz. net wt. (397g)	24

Restricted from sale in CA

AERO-CHEM® NON-CHLORINATED BRAKE CLEANER

- Powerful spray, cleans and degreases fast
- Dries fast and completely
- Leaves no residue
- Helps clean brake dust, grease, oil and brake fluid
- Helps stop disc brake squeal
- For CV joints, clutches, parts and tools
- Flammable

PART #	LEGACY #	DESCRIPTION	QTY.
106520102	PA89391	20oz. Can/15oz. net wt. (425g)	1
110357570	PA89391-12	20oz. Can/15oz. net wt. (425g)	12
116760019	PA89391-24	20oz. Can/15oz. net wt. (425g)	24
116760026	PA89391-720	20oz. Can/15oz. net wt. (425g)	720

Restricted from sale in CA, CO, CT, DE, MD, MI, NH, NY, OH, RI, UT

AERO-CHEM® ULTRA CLEAR LUBE

- Heavy-duty clear aerosol grease
- Designed for applications where a clear, non-staining lubricant
- Temperature range: -30°F to 400°F (-34°C to 204°C)

PART #	LEGACY #	DESCRIPTION	QTY.
113383849	4008545	16oz. Can/13oz. net wt. (369g)	1
116677552	400854S-12	16oz. Can/13oz. net wt. (369g)	12



WARNING: This product can expose you to chemicals including n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

FLEET-FILL® NON-CHLORINATED BRAKE PARTS CLEANER

Quickly removes dirt, grease, brake fluid and grime from brake components; flushes away contaminants without disassembling the brake unit.

Features:

- 10% VOC formula
- VOC Compliant in 50 states
- Hexane Free, 1, 1, 1, Trichloroethane Free
- Extremely flammable
- Color: Colorless
- High pressure spraying
- Fast evaporating

Applications: for use on valve covers, clutch housings, clutch pressure plates and transmission

PART #	LEGACY #	DESCRIPTION	QTY.
115121058	404749	20oz. Can/15oz. net wt. (425g)	1
116683752	404749-12	20oz. Can/15oz. net wt. (425g)	12
116683759	404749-24	20oz. Can/15oz. net wt. (425g)	24



WARNING: This product can expose you to chemicals including Ethyl Benzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Marina & Boat Maintenance Solutions



#102697536 | 122010 KWIK CUT® C/T HOLE SAW MAINTENANCE SET - 5 PC

PART #	LEGACY #	DESCRIPTION	QTY.
101745539	121938	5/8" Kwik Cut® C/T Hole Saw	1
101744159	121940	3/4" Kwik Cut® C/T Hole Saw	1
102698869	121942	7/8" Kwik Cut® C/T Hole Saw	1
102699450	121944	1" Kwik Cut® C/T Hole Saw	1
102702211	121946	1-1/8" Kwik Cut® C/T Hole Saw	1



FLEXZILLA® WATER HOSE (GHT ENDS) **Premium Hybrid Polymer Water Hose**

- Field repairable reusable anodized aircraft aluminum fittings
- Extreme all-weather flexibility
- Spiral bend restrictors for increased flexibility
- Anodized aircraft aluminum male and female GHT fittings
- Maximum working pressure at 70°F: 165 PSI
- Abrasion resistant
- Kink resistant under pressure

PART #	LEGACY #	PRODUCT DESCRIPTION	QTY.
101763154	123553	Flexzilla Water Hose 5/8" I.D. x 50'	1
101763155	123554	Flexzilla Water Hose 5/8" I.D. x 100'	1



NEPTUNE™ 3000

For use on pressure washer machines with working pressures up to 3000 PSI. Rated to temperatures of -20°F to 250°F (-29°C to 121°C).

Tube Nitrile synthetic rubber

Cover Black or blue oil-resistant synthetic rubber, RMA Class B (medium oil resistance)

Reinforcement Braided (1) steel wire

Ends 3/8" male pipe x 3/8" male pipe swivel

PART #	LEGACY #	HOSE COLOR	HOSE ID (IN.)	END CONFIGURATION/ FITTINGS	LENGTH (FT.)	QTY.
116682242	404142	Black	3/8"	3/8" MXMS w/ Kink Guards	50′	1
116682246	404143	Black	3/8"	3/8" MXMS w/ Kink Guards	100′	1
116682249	404144	Blue	3/8"	3/8" MXMS w/ Kink Guards	50′	1
116682251	404145	Blue	3/8"	3/8" MXMS w/ Kink Guards	100′	1



WEATHER-SEAL WRAP

• A clear, plastic film that has an adhesive on one side that is strong enough to hold the wrap in place on almost any surface and seal out contaminants, yet it can be easily removed without pulling off paint, leaving adhesive residue or damaging the surface.



Weather-Seal Wrap

- Seal out rain, snow, wind and dirt
- Use to protect carpet and upholstery from soiling and spills

PART #	DESCRIPTION	QTY.
116717838	24" Wide x 200 ft. Long Rolls	1
116717840	36" Wide x 200 ft. Long Rolls	1






['] MarineWeld™ Syringe

- Specially formulated two-part adhesive system that provides strong, lasting repairs for bonding different or similar surfaces, such as metal, SMC fiberglass and others
- Great for boats, deck and hull accessories
- Uses: Fiberglass, glass, under water/wet and more

PART #	VENDOR PART #	SIZE	STRENGTH	SET TIME	CURE TIME	CURE COLOR	QTY.
121166177	50172	25 ml	2350 PSI	5 minutes	1 hour	White	1







- WaterWeld will plug or seal leaks and patch holes and cracks in almost anything
- Ideal for repairing plumbing, fuel tanks, tub and shower, drains, pool and spa, boats and potable water tanks; setup occurs even under water
- After curing, it can be drilled, tapped, filed, sanded and painted
- Waterproof up to 500 PSI, NSF registered rated

PART #	VENDOR PART #	SIZE	STRENGTH	SET TIME	CURE TIME	CURE COLOR	MAX TEMP	QTY.
121166058	8278U	4oz., 3.5"	2450 PSI	25 minutes	1 hour	Off White	250°F (121°C)	1









Marina & Boat Maintenance Solutions



MINI HOSE CLAMPS - STANDARD

- 300 stainless steel band and housing
- Zinc plated screw 1/4" hex
- 1/4" hex for mini clamps, 5/16" hex for standard clamps

BAND	PART #	# LEGACY #		DART # LECACY # IND		CLAMP	OTV
BAND WIDTH	PAKI#	LEGACY #	NO.	MIN.	MAX.	QTY.	
5/16	106263853	PA81502	6	1/4"	25/32"	10	

STANDARD HOSE CLAMP

- 300 stainless steel band and housing
- Zinc plated screw



RAND			IND.	CLAMP	RANGE	FITS HOSE I.D.	
BAND WIDTH	PART #	LEGACY #	NO.	MIN.	MAX.	RANGE (STD 3/16" WALL)	QTY.
	116742284	PA17786	10	9/16"	1-1/16"	3/8 - 5/8"	10
1/2	116742295	PA17788	16	13/16"	1-1/2"	3/4 - 1"	10
1/2	116742300	PA17790	24	1-1/16"	2"	1-1/4 - 1-1/2"	10
	116742311	PA17792	32	1-9/16"	2-1/2"	1-1/2 - 2"	10

HEAVY DUTY CABLE TIES – BLACK

- Offers a higher tensile strength for heavy load applications
- The bent tail design allows quick and simple installations by hand
- For high volume applications, tensioning tools are available to ensure consistent and safe installation
- Operating Temperature: -40°F to +185°F (-40°C to +85°C)
- Flammability: UL94 V2

PART #	LEGACY #	APPROX. LENGTH	APPROX. WIDTH	MAX BUNDLE DIAMETER	TENSILE STRENGTH	QTY.
110659527	PA16006	15.25"	0.30"	4"	120 lbs.	50

STANDARD CABLE TIES - BLACK

- The economical way to secure bundles from 5/8" to 4" in diameter
- All nylon 6/6 construction features lightweight, high strength, and a wide temperature range
- Continuous operating temperatures -40°F to 185°F (-40°C to 85°C)
- Tensile strength at 73°F dry as molded ASTM D-638 (PSI): 12,000
- UL Flame Rating: 94V-2

PART #	LEGACY #	APPROX. LENGTH	APPROX. WIDTH	MAX BUNDLE DIAMETER	STRENGTH	MILSPEC.	QTY.
106292375	PA16001	11.625"	.15"	3"	40 lbs.	-	100
101723106	10251UZ	8"	.18"	1.97"	50 lbs.	MS3367-1	100
101765137	104058	15.5"	.18"	4"	50 lbs.	MS3367-2	100

KWIK CUT® ALL PURPOSE JOBBER DRILL

- Self-centering 135° split point adds stability to drilling
- Accurate, tight tolerance, perfectly round holes
- Flats on shank provide easy positive chuck grip on sizes 3/16" 1/2"
- Made of high-molybdenum steel

PART #	LEGACY #	DRILL SIZE	DECIMAL EQUIV.	OVERALL LENGTH	FLUTE LENGTH	QTY.
116697602	170245	1/64	.0156	1-3/8	1/2	1
116697605	170246	1/32	.0312	1-3/8	1/2	1
116697608	170247	3/64	.0469	1-3/8	1/2	1
101511715	90139	1/16	.0625	1-7/8	7/8	1
101404174	90140	5/64	.0781	2	1	1
101510373	90141	3/32	.0938	2-1/4	1-1/4	1
101510374	90142	7/64	.1094	2-5/8	1-1/2	1
101468813	90143	1/8	.1250	2-3/4	1-5/8	1
110707230	90144	9/64	.1406	2-7/8	1-3/4	1
101510280	90145	5/32	.1562	3-1/8	2	1
101510037	90146	11/64	.1719	3-1/4	2-1/8	1
101509879	90147	3/16	.1875	3-1/2	2-5/16	1
101511610	90148	13/64	.2031	3-5/8	2-7/16	1
101448544	90149	7/32	.2188	3-3/4	2-1/2	1
101514893	90150	15/64	.2344	3-7/8	2-5/8	1
101510040	90151	1/4	.2500	4	2-3/4	1



PART #	LEGACY #	DRILL SIZE	DECIMAL EQUIV.	OVERALL LENGTH	FLUTE LENGTH	QTY.
110707296	90152	17/64	.2656	4-1/8	2-7/8	1
101512683	90153	9/32	.2812	4-1/4	2-15/16	1
101510041	90154	19/64	.2969	4-3/8	3-1/16	1
101396260	90155	5/16	.3125	4-1/2	3-3/16	1
101468817	90156	21/64	.3281	4-5/8	3-5/16	1
101397192	90157	11/32	.3438	4-3/4	3-7/16	1
101397193	90158	23/64	.3594	4-7/8	3-1/2	1
101511613	90159	3/8	.3750	5	3-5/8	1
101510284	90160	25/64	.3906	5-1/8	3-3/4	1
101511013	90161	13/32	.4062	5-1/4	3-7/8	1
101397195	90162	27/64	.4219	5-3/8	3-15/16	1
101512687	90163	7/16	.4375	5-1/2	4-1/16	1
101510382	90164	29/64	.4531	5-5/8	4-3/16	1
101510381	90165	15/32	.4688	5-3/4	4-5/16	1
101511015	90166	31/64	.4844	5-7/8	4-3/8	1
101405031	90167	1/2	.5000	6	4-1/2	1



Stainless Steel Nipples, Couplers, & Ball Valves



NIPPLE - MALE PIPE THREAD

- Industrial Interchange design
- Available in steel or 303 stainless steel



BODY SIZE (IN.)	THREAD SIZE NPTF	PART # STEEL	LEGACY # STEEL	QTY.	PART # STAINLESS	LEGACY # STAINLESS	QTY.
1/4"	1/4-18	101735182	40047	1	116759070	PA87708	4

COUPLER - FEMALE PIPE THREAD

- Industrial Interchange Design
- Available in Brass or 303 Stainless Steel

Specifications

Body Size 1/4" Rated Pressure (PSI) 300

-40° to 250°F Temperature range

BODY SIZE (IN.)	THREAD SIZE NPTF	PART # BRASS	LEGACY # BRASS	QTY.	PART # STAINLESS	LEGACY # STAINLESS	QTY.
1/4"	1/4-18	101734836	40029	1	106279621	PA87707	1



WARNING: Certain products can expose you to chemicals including Lead and Lead Compounds which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

COUPLER - MALE PIPE THREAD

- Industrial Interchange Design
- Available in Brass or 303 Stainless Steel

Specifications

Body Size 1/4" Rated Pressure (PSI) 300

-40° to 250°F Temperature range

BODY SIZE (IN.)	THREAD SIZE NPTF	PART # BRASS	LEGACY # BRASS	QTY.	PART # STAINLESS	LEGACY # STAINLESS	QTY.
1/4"	1/4-18	101735022	40032	1	116752488	DX-2FM2-S	1



WARNING: Certain products can expose you to chemicals including Lead and Lead Compounds which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to: www.P65Warnings.ca.gov.

316 STAINLESS STEEL BALL VALVES

- 2000 PSIG WOG
- 150 PSI Saturated Steam
- Materials: reinforced TFE stem packing, reinforced TFE stem bearing, A276-316 ball, reinforced TFE seat(2), A276-316 retainer
- Locking handle; 2 piece design
- Full port

PART #	LEGACY #	FEMALE NPT SIZE	QTY.
106258106	PA75159	1/4"	1
106277606	PA75160	3/8"	1
106253718	PA75161	1/2"	1
106256667	PA75162	3/4"	1
106280423	PA75163	1"	1



MARNING: Cancer and Reproductive Harm-www.P65Warnings.ca.gov.









ASSORTMENT PART # 112945118

Customize your Spill Control Station™ with the absorbents you need.



UNIVERSAL GRAY FAMILY

PART #	LEGACY #	DESCRIPTION	QTY.
113253911	404752	Universal Gray Heavy Weight Pads, 15" x 19"	100
116689924	407035	Universal Gray Heavy Weight Pads, 10" x 14"	75
116683775	404753	Universal Gray Medium Weight Pads, 15" x 19"	100
113337474	404754	Universal Gray Heavy Weight Split Roll, 15" x 150'	1
113083231	404755	Universal Gray Medium Weight Split Roll, 15" x 150'	1
116761161	PA91898	Universal Gray Socks, 3" x 4'	30
116683778	404756	Universal Gray Pillows, 18" x 18"	10



OIL-ONLY WHITE FAMILY

PART #	LEGACY #	DESCRIPTION	QTY.
116683781	404757	Oil-Only White Heavy Weight Pads, 15" x 19"	100
116689930	407037	Oil-Only White Heavy Weight Pads, 10" x 14"	75
116683784	404758	Oil-Only White Medium Weight Pads, 15" x 19"	100
113337477	404759	Oil-Only White Heavy Weight Split Roll, 15" x 150'	1
113337478	404760	Oil-Only White Medium Weight Split Roll, 15" x 150'	1
116683787	404761	Oil-Only White Socks, 3" x 4'	30
116681175	104560UZ	Oil-Only White Pillows, 18" x 18"	10



HAZMAT YELLOW FAMILY

PART #	LEGACY #	DESCRIPTION	QTY.
116679424	402289	Hazmat Yellow Heavy Weight Pads, 15" x 19"	100
116689938	407040	Hazmat Yellow Heavy Weight Pads, 10" x 14"	75
116679427	402290	Hazmat Yellow Medium Weight Pads, 15" x 19"	100
113337483	402291	Hazmat Yellow Heavy Weight Split Roll 15" x 150'	1
113337484	402292	Hazmat Yellow Medium Weight Split Roll 15" x 150'	1
116679430	402293	Hazmat Yellow Socks, 3" x 4'	30
116689945	407042	Hazmat Yellow Pillows, 8" x 18"	10



MAXIMIZE EFFICIENCY WITH COMPACT STORAGE SOLUTIONS

Designed to fit seamlessly into smaller workspaces, these innovative cabinets and racks can transform a cluttered, cramped environment into a streamlined productivity powerhouse. Discover the perfect storage solution to suit your facility's unique needs and **take control of your space**. Our products are engineered to help you **make the most of every square inch**, ensuring your marina runs smoothly and efficiently.



Aerosol Can Racks #110488606 | B01068



2 Gallon Flammable Cabinets #116740416 | DM-1002M-50 Manual #116740421 | DM-1002S-50 Self Closing



Utility Cabinet #106524195 | B01069




Chart your course to success with MRO supplies to propel you forward



Every Small Part Counts We're here to manage them for you!®

AppliedMSS.com | 800-458-4018

