

# APPLIED MSS<sup>SM</sup> SHOP SOLUTIONS

FEBRUARY 2026

## ROOTED IN RELIABILITY: Quality Supplies to Help Your Business Grow

### Aero-Chem® PTFE Gel Penetrating Lubricant

- A clear penetrating lubricant that sprays out as a penetrating fluid and sets up to form a tough, heat resistant grease
- Contains PTFE for long lasting lubricity
- Resists water washout
- Temperature range: -30°F to 600°F (-34°C to 316°C)

PART #	DESCRIPTION	QTY.
106273082	20oz. Can/14 oz. net wt. (397g)	1
116758342	20oz. Can/14 oz. net wt. (397g)	12
116758346	20oz. Can/14 oz. net wt. (397g)	24
110357196	20oz. Can/14 oz. net wt. (397g)	600

Restricted from sale in CA



### Aero-Chem® Non-Chlorinated Brake Cleaner

- Powerful spray, cleans and degreases fast
- Dries fast and completely
- Leaves no residue
- Helps clean brake dust, grease, oil and brake fluid
- Helps stop disc brake squeal
- For CV joints, clutches, parts and tools
- Flammable

PART #	DESCRIPTION	QTY.
106520102	20oz. Can/15 oz. net wt. (425g)	1
110357570	20oz. Can/15 oz. net wt. (425g)	12
116760019	20oz. Can/15 oz. net wt. (425g)	24
116760026	20oz. Can/15 oz. net wt. (425g)	720

Restricted from sale in CA, CO, CT, DE, MD, MI, NH, NY, OH, RI, UT



### Fleet-Fill® Non-Chlorinated Brake Parts Cleaner

Quickly removes dirt, grease, brake fluid and grime; flushes away contaminants without disassembling the brake unit.

- 10% VOC formula, VOC Compliant in 50 states
- Hexane Free, 1, 1, 1, Trichloroethane Free
- Extremely flammable
- Color: colorless
- High pressure spraying
- Fast evaporating

PART #	DESCRIPTION	QTY.
115121058	20oz. Can/15 oz. net wt. (425g)	1
116683752	20oz. Can/15 oz. net wt. (425g)	12
116683759	20oz. Can/15 oz. net wt. (425g)	24

**WARNING:** This product can expose you to chemicals including Ethyl Benzene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Aero-Chem® Ultra Clear Lube

- Heavy-duty clear aerosol grease
- Designed for applications where a clear, non-staining lubricant is necessary
- Temperature range: -30°F to 400°F (-34°C to 204°C)

PART #	DESCRIPTION	QTY.
113383849	16oz. Can/13 oz. net wt. (369g)	1
116677559	16oz. Can/13 oz. net wt. (369g)	6
116677552	16oz. Can/13 oz. net wt. (369g)	12
116677556	16oz. Can/13 oz. net wt. (369g)	24

**WARNING:** This product can expose you to chemicals including n-Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### Aero-Chem® Brute Blast®

- Penetrates icy frost, rust, corrosion and releases parts without dismantling
- Loosens rusted nuts and bolts
- Stops rust corrosion
- Displaces moisture

PART #	DESCRIPTION	QTY.
106522909	16oz. Can/11 oz. net wt. (312g)	1
116756695	16oz. Can/11 oz. net wt. (312g)	12
116756700	16oz. Can/11 oz. net wt. (312g)	24

**WARNING:** This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



### CRC® HydroForce® Industrial Strength Degreaser

- An aqueous cleaner with the powerful performance of a solvent
- Removes heavy deposits of grease, oil & dirt
- Biodegradable, concentrated, non-abrasive & non-flammable

PART #	DESCRIPTION	QTY.
116725632	32 fl. oz. (907g) w/Trigger Sprayer	1
121033390	32 fl. oz. (907g) w/Trigger Sprayer	12

Vendor Number 14415

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



# APPLIED MSS<sup>SM</sup> SHOP SOLUTIONS

FEBRUARY 2026



## RESTORE THE SHOWROOM SHINE:

Refresh your field equipment with IPC's professional-grade paint for a high-gloss, factory finish.



## Grip Ties

- Low profile, one-piece fastening
- Reusable, adjustable, releasable and easy to install
- Feature quick release for repetitive access to cable and wire
- Constructed of polyethylene hook and nylon loop material, which is laminated back to back
- Can be opened and closed numerous times without failure



PART #	COLOR	MAX BUNDLE DIAMETER	TENSILE STRENGTH	APPROX. LENGTH (L)	APPROX. WIDTH (W)	HEAD LENGTH (A)	HEAD WIDTH (B)	QTY.
106264158	Red	1.75"	40 lbs.	8"	1.50"	1.5"	1"	10
112100715	Orange	2.625"	40 lbs.	11"	1.50"	1.5"	1"	10
106295750	Blue	2.625"	40 lbs.	11"	1.50"	1.5"	1"	10
116681017	Orange	1"	45 lbs.	6"	.50"	1.5"	1"	10
116681020	Yellow	1"	45 lbs.	6"	.50"	1.5"	1"	10
116681024	Black	1.75"	50 lbs.	8"	.50"	1.5"	1"	10
116681027	Blue	1.75"	50 lbs.	8"	.50"	1.5"	1"	10
102641580	Green	2.63"	55 lbs.	11"	.50"	1.5"	1"	10
116681030	Red	3.88"	60 lbs.	15"	.75"	2.5"	1.5"	10

Multi-color sample pack (1 of each) also available #102643687

**LAUNCH-READY REPAIRS:** Prep your boat for the season with the MarineWeld Syringe. It's the ultimate high-strength, waterproof solution for quick yet permanent marine fixes.



## JB WELD<sup>®</sup> MarineWeld<sup>™</sup> Syringe

- Specially formulated two-part adhesive system that provides strong, lasting repairs for bonding different or similar surfaces, such as metal, SMC fiberglass and others
- Great for boats, deck and hull accessories

PART #	SIZE	STRENGTH	SET TIME	CURE TIME	CURE COLOR	QTY.
121166177	25 ml	2350 PSI	5 minutes	1 hour	White	1

Vendor Number 50172

⚠️ **WARNING:** Cancer. www.P65Warnings.ca.gov.

## JB WELD<sup>®</sup> WaterWeld<sup>™</sup> Epoxy Putty

- WaterWeld will plug or seal leaks and patch holes and cracks in almost anything
- Ideal for repairing plumbing, fuel tanks, tub and shower, drains, pool and spa, boats and potable water tanks; setup occurs even under water
- After curing, it can be drilled, tapped, filed, sanded and painted
- Waterproof up to 500 PSI, NSF registered rated

PART #	SIZE	STRENGTH	SET TIME	CURE TIME	CURE COLOR	MAX TEMP	QTY.
121166058	4 oz., 3.5"	2450 PSI	25 minutes	1 hour	Off White	250°F (121°C)	1

Vendor Number 8278U

\*While supplies last

Digital Catalog available at [Catalog.AppliedMSS.com](http://Catalog.AppliedMSS.com) and in the Google and Android App stores.



**Every Small Part Counts** We're here to manage them for you!®

[AppliedMSS.com](http://AppliedMSS.com) | 800-458-4018