

## SOLUTIONS FOR A STRONGER NEW YEAR

### B'LASTER® Air Tool Conditioner

- Cleans and restores pneumatic tools
- Breaks loose deposits that create friction and impede smooth operation
- Protects tools from freezing down to -25°F (-32°C)

PART #	DESCRIPTION	QTY.
121178960	16 oz. can; 11 oz. net wt. (311 g)	1
121178961	16 oz. can; 11 oz. net wt. (311 g)	12




### Claire® Disinfectant Spray Q

- Hospital grade multipurpose disinfectant for hard, non-porous surfaces
- Soft spot surface sanitizer
- Controls mold and mildew
- Eliminates odors
- Kills 99.9% of germs
- NSF Registered, rated C1

EPA Reg. No. 706-111 has demonstrated effectiveness against viruses similar to 2019 Novel Coronavirus (2019-nCoV) on hard non-porous surfaces. Therefore, Claire® Disinfectant Spray Q can be used against 2019 Novel Coronavirus (2019-nCoV) when used in accordance with the directions for use against Poliovirus type 1 on hard, non-porous surfaces.

Refer to the CDC website <https://www.cdc.gov/coronavirus/2019-ncov/index.html> for additional information.



PART #	DESCRIPTION	SCENT	QTY.
118219502 <sup>▲</sup>	20oz. Can/ 17oz. net wt. (482g)	Country Fresh	1
117398849 <sup>▲</sup>	20oz. Can/ 17oz. net wt. (482g)	Country Fresh	12
118219503 <sup>▲</sup>	20oz. Can/ 17oz. net wt. (482g)	Lemon	1
117398850 <sup>▲</sup>	20oz. Can/ 17oz. net wt. (482g)	Lemon	12

<sup>▲</sup>While Supplies Last.

### SCRUBS® MEDAPHENE® PLUS Disinfectant Wipes

- A water-based formula which ensures surfaces remain wet longer to optimize disinfecting time
- Works quickly not only to loosen, but also absorb contaminants to ensure a clean and disinfected surface
- One-step to sanitize, disinfect and deodorize
- Portable, safe and easy to use
- Each dispensing tub contains 65 pre-moistened towels

**Applications:** On washable hard, nonporous surfaces of bathtubs, toilet seats, exterior toilet bowl surfaces, sinks, faucet handles, showers, glazed tiles, chairs, computer keyboards, desks, doorknobs, light switches, telephones, walls, acrylic, glazed porcelain, metal, finished woodwork, stainless steel, sealed granite and plastic



PART #	DESCRIPTION	QTY.
116683012	7" x 9" (17.78cm x 22.86cm)	1
116683016	7" x 9" (17.78cm x 22.86cm)	6

**VENDOR NUMBER 96365**

**WARNING:** This product can expose you to chemicals including [Ethyl alcohol, 64-17-5], which is [are] known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).



# APPLIED

Maintenance Supplies & Solutions®

### Clorox® Disinfecting Wipes

- Bleach-free, pre-moistened wipes clean and disinfect in one step; kill 99.9% of bacteria, including staph and salmonella
- Each dispensing tub contains 35 pre-moistened towels
- Ideal for day care centers, offices, schools and restaurants
- Citrus blend scent

PART #	DESCRIPTION	QTY.
116682070	7" x 8" (17.78cm x 20.32cm)	1
116682073	7" x 8" (17.78cm x 20.32cm)	12



**VENDOR NUMBER 01594**

Restricted from sale in Canada

### Tork® Everwipe™ Disinfectant Wipes

- Everwipe® Disinfectant Wipes are an EPA registered disinfectant (EPA Reg. No. 1839-190-88331) that are also on the EPA's N-list
- These disinfecting wet wipes are ideal for fast one-step\* cleaning and disinfecting of hard, non-porous surfaces\*\*
- This product comes in an easy to use canister with a convenient flip top lid to keep your wipes moist and is great for on the go cleaning
- 75 1-ply white sheets per canister, 7" L x 7" W



#### Applications:

- "One-step" claim is limited to association with non-food contact surface use.
- When used according to disinfection directions.

Kills SARS-CoV-2 (COVID-19 virus) on hard non-porous surfaces in 30 seconds!

Kills 99.9% of bacteria in just 15 seconds!\*

Kills cold\*\* and flu viruses\*\*\* on hard non-porous surfaces cleans, disinfects\*\*\*\* & deodorizes

#### References:

\*Staphylococcus aureus (Staph), Klebsiella pneumoniae, Listeria monocytogenes, Escherichia coli (E. coli) O157:H7

\*\*Human Coronavirus (ATCC VR-740)

\*\*\*Influenza A Virus, H1N1 Influenza A Virus, Human Coronavirus

\*\*\*\*When used according to disinfection directions

PART #	DESCRIPTION	QTY.
120278435	7" x 7" (17.78cm x 17.78cm)	1
120278436	7" x 7" (17.78cm x 17.78cm)	6



# APPLIED MSS<sup>SM</sup> SHOP SOLUTIONS

JANUARY 2026



## Ratchet P Clamp

### Rugged Bundle Management for Heavy Duty Applications

- Versatility – Secure hard lines, soft cable bundles ranging from 1/4" to 2" wide
- Ease of Use – Position, torque down, close by hand – that's it!
- Alignment – Center cables as the clamp closes
- Durability – PA66 body and high grade steel mounting plate never wears out or corrodes
- Designed for heavy duty manufacturing, automotive and solar installations
- Straight mounting plate



114242181



## Straight Steel Mounting Plate

PART #	BUNDLE DIAMETER	HOLE SIZE	QTY.
114242181	.24"-.54"	M6 / .256"	10
114242182	.52"-.77"	M6 / .256"	10
116690276	.76"-1.42"	M6 / .256"	10
114242184	1.42"-2.01"	M6 / .256"	10
116688748	.24"-.54"	M8 / .327"	10
116688751	.24"-.54"	M10 / .405"	10
116688754	.24"-.54"	M12 / .510"	10
116688757	.52"-.77"	M8 / .327"	10
116688760	.52"-.77"	M10 / .405"	10
116688763	.52"-.77"	M12 / .510"	10
116688765	.76"-1.42"	M8 / .327"	10
116688768	.76"-1.42"	M10 / .405"	10
116688770	.76"-1.42"	M12 / .510"	10
116688773	1.42"-2.0"	M8 / .327"	10
116688775	1.42"-2.0"	M10 / .405"	10
116688778	1.42"-2.0"	M12 / .510"	10

## Straight 304 Stainless Steel Mounting Plate

PART #	BUNDLE DIAMETER	HOLE SIZE	QTY.
114242185	.24"-.54"	M6 / .256"	10
114242186	.24"-.54"	M8 / .327"	10
114242187	.24"-.54"	M10 / .405"	10
114242188	.50"-.77"	M6 / .256"	10
114242189	.50"-.77"	M8 / .327"	10
114242190	.50"-.77"	M10 / .405"	10
114242191	.76"-1.42"	M6 / .256"	10
114242192	.76"-1.42"	M8 / .327"	10
114242193	.76"-1.42"	M10 / .405"	10
114242194	1.42"-2.01"	M6 / .256"	10
114242195	1.42"-2.01"	M8 / .327"	10
114242196	1.42"-2.01"	M10 / .405"	10

## 90° Steel Mounting Plate

- Zip clamp
- 90° angle mounting plate

PART #	BUNDLE DIAMETER	HOLE SIZE	QTY.
114242108	.24"-.54"	.327"	10
114242109	.24"-.54"	.405"	10
114242111	.52"-.77"	.327"	10
114242112	.52"-.77"	.405"	10
114242174	.76"-1.42"	.327"	10
114242175	.76"-1.42"	.405"	10
114242177	1.42"-2.01"	.327"	10
114242178	1.42"-2.01"	.405"	10



## General Purpose Grade, Colored Cloth Duct Tape



- General purpose, contractor grade, colored cloth duct tape
- Conformable
- Cold temperature adhesion
- Will not twist or curl during application
- Waterproof backing
- 30-day indoor, clean removal
- Service temperature range: 35°F to 200°F (2°C to 93°C)

PART #	SIZE	COLOR	MIL	TENSILE STRENGTH	QTY.
121149195	2 in x 60 yd.	Black	9	26 lbs	1
121149196	2 in x 60 yd.	Blue	9	26 lbs	1
121149197	2 in x 60 yd.	Red	9	26 lbs	1
121178959	2 in x 60 yd.	Green	9	26 lbs	1

## Ratchet Clamp Inserts

- Zip clamp soft insert
- Provides an extra layer of protection for high vibration uses and cable/hose bundles that are soft or brittle

PART #	BUNDLE DIAMETER	QTY.
116689804	.24"-.54"	10
116689807	.52"-.77"	10
116689811	.76"-1.42"	10
116689813	1.42"-2.01"	10



### Global Full Port 600WOG (Water, Oil, Gas) Forged Brass Ball Valve

- Suitable for full range of liquids and gases
- Pressure rated at 600PSI (42 bars) WOG (non-shock) and 150 WSP (10.34 bars) saturated steam.
- PTFE stem packing seal, thrust washer and seats.
- Adjustable stem packing gland
- Maximum operating temperature: 302°F (150°C)
- Minimum operating temperature: -22°F (-30°C)
- Forged brass - for more strength
- Threaded ends to ANSI B1.20.1



600 PSI non-shock cold water, gas, oil  
150 PSI saturated steam

PART #	FEMALE NPT SIZE	QTY.
101790705	1/4"	1
102680151	3/8"	1
101769027	1/2"	1
101768790	3/4"	1
101816282	1"	1
101791016	1-1/4"	1
101790706	1-1/2"	1



**WARNING:** Certain products can expose you to chemicals including Lead and Lead Compounds which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to: [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### Booster Cable Sets Extra Heavy Duty

- 4 ga. welding cable stranding
- Heavy duty 500 AMP clamp
- Cable remains flexible at sub-zero temperatures
- Tangle-free, twin-line cable design



PART #	GAUGE	LENGTH	JACKET COLOR	O.D.	CLAMP	QTY.
102720777	4 ga.	20'	Black/White	.425	500 AMP	1

**WARNING:** This product can expose you to chemicals including [Vinyl Chloride, DIDP, DEHP], which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Digital Catalog available at [Catalog.AppliedMSS.com](http://Catalog.AppliedMSS.com) and in the Google and Android App stores.



**Every Small Part Counts** We're here to manage them for you!®

**AppliedMSS.com | 800-458-4018**

### 316 Stainless Steel Locking Handle Ball Valves

- 2000 PSI WOG
- 150 PSI saturated steam
- Materials: reinforced TFE stem packing, reinforced TFE stem bearing, A276-316 ball, reinforced TFE seat(2), A276-316 retainer
- Locking handle; 2 piece design

PART #	FEMALE NPT SIZE	PORT SIZE	QTY.
106258106	1/4"	Full Port	1
106277606	3/8"	Full Port	1
106253718	1/2"	Full Port	1
106256667	3/4"	Full Port	1
106280423	1"	Full Port	1



**WARNING:** Cancer and Reproductive Harm-[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### DID YOU KNOW

At 0°F, a lead-acid battery has only about 40% of the cranking power it has at 80°F, yet the engine requires significantly more power to turn over due to thickened oil. When jump-starting in extreme cold, the gauge (thickness) of your booster cables is critical. Heavy-duty 4-gauge welding cable stranding allows for a high current flow with minimal resistance, ensuring that the limited power available is delivered efficiently to the dead battery without the cables overheating or losing flexibility.

